


1. Device Name	SMS BOOT COVER											
2. Description	Pro-Val SMS Boot Cover provides an excellent protection barrier between footwear and the environment. Made from triple layer SMS, the Boot Covers are strong and breathable and feature a vinyl non skid sole.											
3. Product Codes & Sizes	<table border="1" data-bbox="199 414 1141 504"> <thead> <tr> <th>Product Code</th> <th>Colour</th> <th>Fabric Weight</th> <th>Shipper Barcode</th> </tr> </thead> <tbody> <tr> <td>50509</td> <td>WHITE</td> <td>48gsm</td> <td>19311059505094</td> </tr> </tbody> </table>				Product Code	Colour	Fabric Weight	Shipper Barcode	50509	WHITE	48gsm	19311059505094
Product Code	Colour	Fabric Weight	Shipper Barcode									
50509	WHITE	48gsm	19311059505094									
4. Recommended Applications	<ul style="list-style-type: none"> • Asbestos Removal • Demolition • Medical • Laboratory • Hospitals • Emergency Services • Forensic • Diagnostic • Veterinary • Aged Care • Protection for Floors, Carpet & Tiles • Clean Room Environment • Food Manufacturing • Food Processing • Clean Room Environment • Industrial • Manufacturing • Maintenance 											
5. Materials	Non Woven Polypropylene 48gsm, spunbond, meltblown and spunbond triple layer matrix											
6. Standards & Approvals	 <p>SMS Boot Cover is tested to and complies with;</p> <ul style="list-style-type: none"> • Certified under HACCP Food Safety Accreditation 											
7. Specifications	<ul style="list-style-type: none"> • SMS Triple layer limited use overboot designed to cover feet and footwear to shin. To protect product and areas from contaminants potentially brought in on street clothes from external areas. Alternatively to protect street clothes from contaminants in working area • Protects against water based splashes and sprays, particulate matter, fibres, dust, dirt, grease and grime • Vinyl non-skid sole • Splash resistant • Stitched ties for ankle, elastic at top • Good tear resistance • Suitable for outdoor use • One size fits all • Inflammable, not flame resistant, melts at around 120°C • Available in white only 											
8. Packaging	50 Pieces per Polybag, 4 Polybags per Carton TOTAL 200 Pieces per Carton											
9. Shipper Carton Specifications	<table border="1" data-bbox="199 1601 981 1713"> <thead> <tr> <th>LENGTH (mm)</th> <th>WIDTH (mm)</th> <th>HEIGHT (mm)</th> <th>GROSS WEIGHT (kg)</th> </tr> </thead> <tbody> <tr> <td>430</td> <td>430</td> <td>360</td> <td>7.8</td> </tr> </tbody> </table>				LENGTH (mm)	WIDTH (mm)	HEIGHT (mm)	GROSS WEIGHT (kg)	430	430	360	7.8
LENGTH (mm)	WIDTH (mm)	HEIGHT (mm)	GROSS WEIGHT (kg)									
430	430	360	7.8									
10. Washing Instructions	Not Recommended - do not launder or iron, single use only											
11. Storage Conditions	Store out of direct sunlight in dry conditions between 10 °c and 30 °c.											
12. Suitability	The end-user to determine the suitability of the product for their application											

