


<b>1.</b> Device Name	<b>CRIMPED BERET</b>																											
<b>2.</b> Description	Non Woven Polypropylene, Soft and Lightweight, Breathable, Air Permeable, Latex Elastic Perimeter, Available in 21" and 24"																											
<b>3.</b> Product Codes & Sizes	<table border="1"> <thead> <tr> <th>Product Code</th> <th>Colour</th> <th>Packaging</th> <th>Shipper Barcode</th> </tr> </thead> <tbody> <tr> <td>DPEB21</td> <td>WHITE 21"</td> <td>100 pcs per polybag</td> <td>19311059500129</td> </tr> <tr> <td>DPEB21B</td> <td>BLUE 21"</td> <td>100 pcs per polybag</td> <td>19311059500143</td> </tr> <tr> <td>DPEB21G</td> <td>GREEN 21"</td> <td>100 pcs per polybag</td> <td>19311059500167</td> </tr> <tr> <td>DPEB21R</td> <td>RED 21"</td> <td>100 pcs per polybag</td> <td>19311059500181</td> </tr> <tr> <td>DPEB24</td> <td>WHITE 24"</td> <td>100 pcs per polybag</td> <td>19311059500204</td> </tr> </tbody> </table>				Product Code	Colour	Packaging	Shipper Barcode	DPEB21	WHITE 21"	100 pcs per polybag	19311059500129	DPEB21B	BLUE 21"	100 pcs per polybag	19311059500143	DPEB21G	GREEN 21"	100 pcs per polybag	19311059500167	DPEB21R	RED 21"	100 pcs per polybag	19311059500181	DPEB24	WHITE 24"	100 pcs per polybag	19311059500204
Product Code	Colour	Packaging	Shipper Barcode																									
DPEB21	WHITE 21"	100 pcs per polybag	19311059500129																									
DPEB21B	BLUE 21"	100 pcs per polybag	19311059500143																									
DPEB21G	GREEN 21"	100 pcs per polybag	19311059500167																									
DPEB21R	RED 21"	100 pcs per polybag	19311059500181																									
DPEB24	WHITE 24"	100 pcs per polybag	19311059500204																									
<b>4.</b> Recommended Applications	<ul style="list-style-type: none"> <li>Food Processing</li> <li>Food Service</li> <li>Food Manufacturing</li> <li>Industrial</li> <li>Hair and Beauty</li> <li>Aged Care</li> <li>Medical</li> <li>Hospitals</li> <li>Dental</li> <li>Laboratory</li> <li>Manufacturing</li> <li>Seafood Industry</li> <li>Abattoirs &amp; Meatworks</li> <li>Bakeries</li> <li>Beverage Industry</li> <li>Poultry Works</li> <li>Fisheries</li> <li>Veterinary</li> </ul>																											
<b>5.</b> Materials	Polypropylene and colour pigment																											
<b>6.</b> Standards & Approvals	 <p><b>Crimped Beret</b> is tested to and complies with;</p> <ul style="list-style-type: none"> <li>Certified under HACCP Food Safety Accreditation</li> </ul>																											
<b>7.</b> Specifications	<ul style="list-style-type: none"> <li>Limited use protective clothing designed to contain *head hair and protect from human hair and scalp shed</li> <li>Made from non-woven polypropylene 10gsm and elastic</li> <li>Soft and lightweight</li> <li>Breathable, air permeable</li> <li>Protects against particulate matter, fibres, dirt, dust, grease and grime</li> <li>This product has no water resistance</li> <li>Inflammable, not flame resistant. Melts at around 120°C</li> <li>Do not launder or iron</li> <li>*Very long hair may first need to be tied up and pinned</li> </ul>																											
<b>8.</b> Packaging	100 pieces per Polybag, 10 Polybags per Carton TOTAL 1000 Crimped Berets per Carton																											
<b>9.</b> Shipper Carton Specifications	<table border="1"> <thead> <tr> <th>SIZE</th> <th>LENGTH (mm)</th> <th>WIDTH (mm)</th> <th>HEIGHT (mm)</th> <th>GROSS WEIGHT (kg)</th> </tr> </thead> <tbody> <tr> <td>21"</td> <td>330</td> <td>230</td> <td>260</td> <td>4.0</td> </tr> <tr> <td>24"</td> <td>330</td> <td>250</td> <td>270</td> <td>4.5</td> </tr> </tbody> </table>				SIZE	LENGTH (mm)	WIDTH (mm)	HEIGHT (mm)	GROSS WEIGHT (kg)	21"	330	230	260	4.0	24"	330	250	270	4.5									
SIZE	LENGTH (mm)	WIDTH (mm)	HEIGHT (mm)	GROSS WEIGHT (kg)																								
21"	330	230	260	4.0																								
24"	330	250	270	4.5																								
<b>10.</b> Washing Instructions	Not Recommended - do not launder or iron, single use only																											
<b>11.</b> Storage Conditions	Store out of direct sunlight in dry conditions between 10 °c and 30 °c.																											
<b>12.</b> Suitability	The end-user to determine the suitability of the product for their application																											

