





LED Bulkhead

The Aqua3 LED Bulkhead is the latest addition to the bulkhead family. Suitable for BESA box, side and rear entry, a versatile solution for commercial premises.

- The ideal replacement for 28W 2D Fittings
- Integral motion sensor options
- No lamp replacement
- No maintenance
- Opal diffuser
- 35000 hour life
- Ø325 mm x 100 mm
- Sealed durable fitting
- Suitable for BESA box, side and rear entry



LMR80: Maximum 20% of lumen depreciation over rated hours.
B10: Maximum 10% of fittings failure rate over rated hours



technical@belllighting.co.uk
sales@belllighting.co.uk



LED Bulkhead

Technical Specification

Construction	Polycarbonate body and lens
Driver	BELL
LED Chip	Samsung
IP Rating	IP65
Operating Temp	-20°C to +35°C
Input Voltage	220 - 240V
Power Factor	> 0.9
CRI	85 - Exceeds EU standard of Ra 80 for Colour Rendering Index
LMR	80 - Exceeds EU standard of 70 for Lumens Maintenance Ratio

Code	W	Description	Lm	Temp	Hours
10883	13	Aqua3 LED Bulkhead Standard Version (No Sensor)	1200	4000K	35000
10887	13	Aqua3 LED Bulkhead Standard Version (No Sensor) Emergency 3 hour maintained	1200	4000K	35000
10891	13	Aqua3 LED Bulkhead Microwave Version On/Off with Presence Detection	1200	4000K	35000
10895	13	Aqua3 LED Bulkhead Microwave Version On/Off with Presence Detection. Emergency 3 hour maintained	1200	4000K	35000

Microwave Max Operating Height 3.2m

Emergency versions must be tested in line with the requirements of BS5266, failure to do so may effect battery life and warranty

¹ Exceeds EU standard of 70 for Lumens Maintenance Ratio

² Exceeds EU standard of RA 80 for Colour Rendering Index

³ Subject to terms & conditions (Contact Customer Service)

