NOBILE
Italia

9094

PLASTER DOWNLIGHT





50°

H (m)	D (m)	Emax (lx)	Eav (lx)
1.0	1.0	812	446
2.0	1.9	203	112
3.0	2.8	90	50

For further information please visit www.nobile.it/en/

IP20

SPECIFICATION TEXT

Plaster round frame for recessed-mounted trimless installation in plasterboard ceiling from 6 to 15mm height. Fixed emission. Trimless effect. Acid-etched glass diffuser. IP20. GU10 lamp holder included, suitable for LED lamp max 8W, not included. Dimensions: diameter 120mm, height 55mm. Suitable for IP64 LED module, to be ordered separately.

Mounting	Product type	**Plaster downlight**
	Installation type	**Recessed-mounted in plasterboard ceiling**
Dimension	Diameter	**120mm**
	Height	**55mm**
	Cut-out	**125mm**
Lamp	Lamp LED	**max 8W, not included**
	Module LED	**D1/DUO IP64 to be ordered separately**
Material	Body	**Plaster**
	Diffuser	**Acid-etched glass**
	Bracket	**Aluminium**
	Screws	**Steel**
Accessories	Included	**Lamp holder GU10** **Adjustable bracket according to the ceiling thickness - variable dimension from 6 to 15mm (*)**
Warranty	Warranty	**2 years**
Norms	Norm compliance	**EN60598-1, EN60598-2-2**

LED MODULE AVAILABLE

Code ON-OFF driver	Code PUSH driver	Code DALI driver	Nominal/lm	LED/W	System/W	CCT	Beam
D1/DUO/20/2K/6	**D1/DUO/20/2K/2P**	**D1/DUO/20/2K/3**	840	8.5	9.5	2700K	20°
D1/DUO/20/3K/6	**D1/DUO/20/3K/2P**	**D1/DUO/20/3K/3**	890	8.5	9.5	3000K	20°
D1/DUO/20/4K/6	**D1/DUO/20/4K/2P**	**D1/DUO/20/4K/3**	960	8.5	9.5	4000K	20°
D1/DUO/40/2K/6	**D1/DUO/40/2K/2P**	**D1/DUO/40/2K/3**	840	8.5	9.5	2700K	40°
D1/DUO/40/3K/6	**D1/DUO/40/3K/2P**	**D1/DUO/40/3K/3**	890	8.5	9.5	3000K	40°
D1/DUO/40/4K/6	**D1/DUO/40/4K/2P**	**D1/DUO/40/4K/3**	960	8.5	9.5	4000K	40°
D1/DUO/55/2K/6	**D1/DUO/55/2K/2P**	**D1/DUO/55/2K/3**	840	8.5	9.5	2700K	55°
D1/DUO/55/3K/6	**D1/DUO/55/3K/2P**	**D1/DUO/55/3K/3**	890	8.5	9.5	3000K	55°
D1/DUO/55/4K/6	**D1/DUO/55/4K/2P**	**D1/DUO/55/4K/3**	960	8.5	9.5	4000K	55°



LED CREE

Lifetime 50.000h (L80B10). Module in anodized aluminium.

Module LED IP64.

Lens 20° in polycarbonate, 40° and 55° in PMMA.

ON-OFF driver included.

Nobile Italia S.p.A.
Viale Alexandre Gustave Eiffel, 100 Commercity Isola P.21-24 - 00148 Roma, Italia - Tel. +39 06 65002524 - info@nobile.it
Export Sales Department: Via Lavoratori Autobianchi, 1 20832 Desio (MB), Italia - Tel. +39 0362 1790030 - export.dpt@nobile.it