

93101

OUTDOOR PROJECTOR

H (m)	D (m)	E _{max} (lx)	E _{av} (lx)
2.0	1.6	1134	636
4.0	3.2	283	159
6.0	4.8	126	71

For further information please visit www.nobile.it/en/

SPECIFICATION TEXT



Outdoor LED projector with bracket and spike for installation on floor or ground. Anodized aluminium body. Transparent tempered glass. IK08. IP65. Adjustable 0-180° tilt. Neoprene H05RN-F 3x1.5mm² cable of 1500mm. 220-240V - 50/60Hz power supply included.

Mounting	Product type	Outdoor projector with bracket and spike							
	Installation type	Floor or ground-installed through bracket or spike							
Dimension	Body diameter	105mm							
	Body length	186mm							
	Height	138mm							
Lamp	LED	CREE							
	System/W	29W							
	Luminous flux nominal	93101/15/3K	2600lm	93101/15/4K	3300lm	93101/28/3K	2600lm	93101/28/4K	3300lm
		93101/42/3K	2600lm	93101/42/4K	3300lm				
	Luminous flux real	93101/15/3K	2008lm	93101/15/4K	2547lm	93101/28/3K	2635lm	93101/28/4K	3344lm
		93101/42/3K	2566lm	93101/42/4K	3256lm				
	Colour temperature CCT	3000K, 4000K							
	Colour rendering index CRI	>80							
	LED Lifetime	50.000 h							
Light	MacAdam	3							
	Adjustability	0-180° rotation / 0° tilt							
	Light distribution	Direct							
	Light beam	15°, 28°, 42°							
Material	Body	Anodized aluminium							
	Diffuser	Transparent tempered glass							
	Spike	Plastic (included)							
	Screws	Stainless steel							
	Cable	Neoprene H05RN-F 3x1,5mm ² 1500mm							
IK	IK	08							
Electrical	Operating voltage	220-240V 50-60Hz power supply included							
Warranty	Warranty	3 years							
Norms	Norm compliance	EN60598-1, EN60598-2-1, EN61000-3-3, EN61000-3-2, EN61547, EN55015							

CONFIGURAZIONE CODICE

93101	/	*	*	/	*	*
		1			2	
1	Light beam	15 = 15°; 28 = 28°; 42 = 42°				
2	Colour temperature	3K = 3000K; 4K = 4000K.				