



A8



OUTDOOR PROJECTOR






H (m)	D (m)	E _{max} (lx)	E _{av} (lx)
1.5	1.1	328	192
1.0	0.7	738	432
0.5	0.4	2951	1727

For further information please visit www.nobile.it/en/

SPECIFICATION TEXT



LED projector with adjustable bracket for ground, wall or ceiling installation. OSRAM LED. Lifetime 50.000h (70% lumen maintenance). Body and bracket are in aluminium. Neoprene H05RN-F 2x0,75mm² cable of 3m. IP68. Power supply not included. **PICCHETTO/A8** Ground spike mm.170 to be ordered separately

Mounting	Product type	Outdoor projector with bracket			
	Installation type	Floor or ground-installed through bracket or spike			
Dimension	Body diameter	68mm			
	Body length	54mm			
Lamp	LED	OSRAM			
	System/W	6W			
	Luminous flux nominal	A8	660lm	A8/4K	720lm
	Luminous flux real	A8	486lm	A8/4K	519lm
	Colour temperature CCT	3000K, 4000K			
	Colour rendering index CRI	>80			
	LED Lifetime	50.000 h			
	MacAdam	3			
Light	Adjustability	0° rotation / 130° tilt			
	Light distribution	Direct			
	Light beam	40°			
Material	Body	Anodized aluminium			
	Diffuser	Transparent tempered glass			
	Spike	Plastic (included)			
	Screws	Stainless steel			
	Cable	Neoprene H05RN-F 2x0.75mm² 3m			
IK	IK	07			
Electrical	Operating voltage	24Vdc			
Warranty	Warranty	3 years			
Norms	Norm compliance	EN60598-1, EN60598-2-1, EN61000-3-3, EN61000-3-2, EN61547, EN55015			

CODE COFIGURATION

A8	/	*	*
1	Colour temperature	no extension 3000K; 4K = 4000K.	1