



BRIK PRO - BP22/2B



BI-EMISSION WALL LIGHTING



SPECIFICATION TEXT



Rectangular outdoor LED luminaire for wall-mounted installation. Bi-emission lighting, 20°x30° light beam. Die-cast aluminium body painted white (RAL9003), grey (RAL9006), anthracite (RAL7016) or dark brown. Efficient flow and controlled luminance. High visual comfort CRI>90. Black silk-screened glass covering PMMA lens. IK10. IP67. IP68 waterproof connector. Reduced dimensions: length 220mm, depth 33mm, height 110mm. 220-240V - 50/60Hz power supply included.

Mounting	Product type	Outdoor wall-mounted luminaire			
	Installation type	Wall-mounted			
Dimension	Body	110x220mm			
	Width	33mm			
Lamp	LED	CREE			
	System/W	2x14W			
	Luminous flux nominal	BP22/2B/3K/_	2x1300lm	BP22/2B/4K/_	2x1400lm
	Luminous flux real	BP22/2B/3K/_	2x958lm	BP22/2B/4K/_	2x1022lm
	Colour temperature CCT	3000K, 4000K			
	Colour rendering index CRI	>90			
	LED Lifetime	50.000 h			
Light	Light distribution	Direct and indirect			
	Light beam	20x30°			
Material	Body	Die-cast aluminium			
	Colour	A= anthracite RAL7016, G= grey RAL9006, W= white RAL9003, BR= dark brown			
	Diffuser	Black silk-screened glass			
	Lens	PMMA			
	Screws	Steel			
IK	IK	10			
Electrical	Operating voltage	220-240V 50-60Hz power supply included			
Warranty	Warranty	3 years			
Norms	Norm compliance	EN60598-1, EN60598-2-1, EN62471, IEC/TR 62778, EN61000-3-3, EN61000-3-2, EN61547, EN55015			

CODE CONFIGURATION

BP22	/	2B	/	*	*	/	*
				1			2
1	Colour temperature		3K = 3000K; 4K = 4000K.				
2	Colour		A= anthracite; G= grey; W= white; BR= dark brown				

