

BRIDGE BG01

RECESSED LINEAR STRUCTURE

For further information please visit www.nobile.it/en/


SPECIFICATION TEXT




Linear structure in polystyrene and PVC for recessed installation in plasterboard 12,5mm depth. The product code includes: 2 pcs of 1000mm of structure, 2 pcs of 1000mm of aluminum profile for LED strip with opal PC diffuser and 2 pcs of 1000mm of neoprene sheath to protect the 3M adhesive provided for gluing the aluminum profile after plastering. Fixing to the structure using screws for plasterboard (not included). Available version with 45° cut on one side to realise 90° corner horizontal. Suitable even in damp areas (by using compatible outdoor strips).

Mounting	Product type	Linear structure for recessed installation	
	Installation type	Linear lighting for wall and ceiling	
Dimension	Length	1000mm	
	Width	100mm	
	Height	12.5mm	
	Surface for LED	17.5mm	
	Weight	435g/m	
	Material	Structure	Polystyrene and PVC
Profile		Aluminium (BARRA/STRIP/3E model)	
Diffuser		PC opal	
Type of diffuseur (included)		BG/01/S	Linear cut profile
		BG/01/LA/S	Angular profile
Diffuser transparency		Opal	-25% of luminous flux
Accessories	Included	2 pcs aluminium profile 1000mm with opal diffuser	
		2 pcs neoprene sheath 1000mm	
	Not included	DIF.B/STRIP/3E/S	Opal diffuser L.2m
		DIFF/5M/S	Opal diffuser roll L.5m
DIFF/10M/S		Opal diffuser roll L.10m	
Warranty	Warranty	5 years	

BG/01/S



BG/01/LA/S



LED strip compatibility																				
	48092	50041	50092	70002	70042	70092	80160	80200	80300	80340	80360	80390	80400	80500	48102	50051	50102	70012	70052	70102
BARRA/STRIP/3E	✓	✓	✓	✓	✓	✓	✗	✓	✓	✓	✗	✓	✗	✗	✓	✓	✗	✓	✓	✗
	INDOOR LIGHT										OUTDOOR LIGHT					COLOUR LIGHT				