



COMBO - C3R



ROUND FIXED WITH FRAME



SPECIFICATION TEXT

Round recessed LED luminaire with fixed optics and perimeter surface frame. Efficient flow and controlled luminance UGR<16 (30°) or UGR<22 (60°). Deep recessed design with high visual comfort CRI>90. IP20/IP 54. 3 polycarbonate reflector colours available. Magnetic fixing system for reflector mounting. Adjustable fixing brackets for ceiling depths from 1mm to 12,5mm. Power supply included, dimmable versions and remote control options available. Compliant with CAM EDILIZIA standards, minimum environmental criteria. (Ministerial Decree of June 23, 2022).

Mounting	Product type	Recessed fixed downlight
	Installation type	Ceiling
Dimension	Diameter	218mm
	Height	132mm
	Cut out	200mm
	Minimum recessed depth	185mm
	Plasterboard depth	min. 1mm max. 25mm
Lamp	LED	Citizen COB
	LED/W	25W, 38W or 52W
	System/W	28W, 42W or 56W
	Luminous flux nominal	C3R/M/3K25/_ 3300lm C3R/M/4K25/_ 3500lm C3R/M/3K38/_ 4600lm C3R/M/4K38/_ 4900lm C3R/M/3K52/_ 5600lm C3R/M/4K52/_ 5800lm C3R/F/3K25/_ 3300lm C3R/F/4K25/_ 3500lm C3R/F/3K38/_ 4600lm C3R/F/4K38/_ 4900lm C3R/F/3K52/_ 5600lm C3R/F/4K52/_ 5800lm
	Luminous flux real	C3R/M/3K25/_ 2781lm C3R/M/4K25/_ 2950lm C3R/M/3K38/_ 3876lm C3R/M/4K38/_ 4129lm C3R/M/3K52/_ 4896lm C3R/M/4K52/_ 5071lm C3R/F/3K25/_ 2264lm C3R/F/4K25/_ 2401lm C3R/F/3K38/_ 3156lm C3R/F/4K38/_ 3362lm C3R/F/3K52/_ 3841lm C3R/F/4K52/_ 3979lm
	Colour temperature CCT	3000K, 4000K
	Colour rendering index CRI	>90
	LED Lifetime	50.000 h L70B10 (Ta 25°)
	MacAdam	3
	UGR	<16 (30°) - <22 (60°)
Light	Adjustability	0° rotation / 0° tilt
	Light distribution	Direct
	Light beam	30°, 60°
Material	Body	Die-cast aluminium
	Frame	Aluminium painted white (RAL9016)
	Reflector	Polycarbonate. Colours black, silver matt or white
Electrical	Driver	220-240V 50-60Hz included
	LED current	700mA, 1050mA or 1400mA
Warranty	Warranty	5 years
Norms	Norm compliance	EN60598-1, EN60598-2-2, EN62471, IEC/TR 62778, EN62493, EN61000-3-3, EN61000-3-2, EN61547, EN55015

CODE CONFIGURATION

C	*	*	/	*	/	*	*	*	*	/	*	*
	1	2		3		4		5			6	7
1	Product dimension											
2	Frame											
3	Light beam											
4	Colour temperature											
5	Power W											
6	Colour reflector											
7	Driver **											

** 9-10-11 not available for 7.5W, 9W and 52W versions
* Max 4 devices PUSH button

Emergency kit available upon request

KIT/EMERGENZA/3H	Emergency kit for LED up to 3 hours
------------------	-------------------------------------