



COMBO - C3S



SQUARE FIXED WITH FRAME



SPECIFICATION TEXT

Square recessed LED luminaire with fixed optics and perimeter surface frame. Efficient flow and controlled luminance. Deep recessed design with high visual comfort CRI>90. IP20/IP54. 3 polycarbonate reflector colours available. Magnetic fixing system for reflector mounting. Adjustable fixing brackets for ceiling depths from 1mm to 12,5mm. Power supply included, dimmable versions and remote control options available. Compliant with CAM EDILIZIA standards, minimum environmental criteria. (Ministerial Decree of June 23, 2022).

Mounting	Product type	Recessed fixed downlight							
	Installation type	Ceiling							
Dimension	Body	220x220mm							
	Height	132mm							
	Cut out	200x200mm							
	Minimum recessed depth	185mm							
	Plasterboard depth	min. 1mm max. 25mm							
Lamp	LED	Citizen COB							
	LED/W	25W or 38W							
	System/W	28W or 42W							
	Luminous flux nominal	C3R/F/3K25/_	3300lm	C3R/F/4K25/_	3500lm	C3R/F/3K38/_	4600lm	C3R/F/4K38/_	4900lm
	Luminous flux real	C3R/F/3K25/_	2264lm	C3R/F/4K25/_	2401lm	C3R/F/3K38/_	3156lm	C3R/F/4K38/_	3362lm
	Colour temperature CCT	3000K, 4000K							
	Colour rendering index CRI	>90							
	LED Lifetime	50.000 h L70B10 (Ta 25°)							
	MacAdam	3							
Light	UGR	<22 (60°)							
	Adjustability	0° rotation / 0° tilt							
	Light distribution	Direct							
	Light beam	60°							
Material	Body	Die-cast aluminium							
	Frame	Aluminium painted white (RAL9016)							
	Reflector	Polycarbonate. Colours black, silver matt or white							
Electrical	Driver	220-240V 50-60Hz included							
	LED current	700mA or 1050mA							
Warranty	Warranty	5 years							
Norms	Norm compliance	EN60598-1, EN60598-2-2, EN62471, IEC/TR 62778, EN62493, EN61000-3-3, EN61000-3-2, EN61547, EN55015							

CODE CONFIGURATION

C	*	*	/	*	/	*	*	*	*	/	*	*
	1	2		3		4		5			6	7
1	Product dimension		0 = 75mm ; 1 = 100mm; 2 = 150mm; 3 = 200mm.									
2	Frame		R = round; S = square.									
3	Light beam		M = 25°; F = 50°.									
4	Colour temperature		3K = 3000K; 4K = 4000K.									
5	Power W		(C0) 07 or 11 ; (C1) 9 or 13 ; (C2) 18 or 25 ; (C3) 25, 38 or 52 .									
6	Colour reflector		B = black; M = silver matt; W = white.									
7	Driver **		1 = On-Off Made in Italy; 2* = PUSH/1-10V Made in Italy; 3 = DALI Made in Italy; 6 = On-Off; 9 - Wi-Fi ZIGBEE Made in Italy (Zigbee gateway, not included); 10 - Bluetooth BLL Made in Italy (by APP BLL PLUS: IOS/Android); 11 - Bluetooth CASAMBI Made in Italy (by APP CASAMBI: IOS/Android)									

\*\* 9-10-11 not available for 7.5W, 9W and 52W versions
\* Max 4 devices PUSH button

Emergency kit available upon request

KIT/EMERGENZA/3H	Emergency kit for LED up to 3 hours
------------------	-------------------------------------