

DL013/S

SQUARE CEILING-MOUNTED

For further information please visit www.nobile.it/en/

SPECIFICATION TEXT



Indoor LED square luminaire for ceiling-mounted installation. White or black painted aluminium body. CRI>80. 24°, 40°, 50° light beams available. Chrome polycarbonate reflector. Micro-prismatic diffuser. Dimensions: length 86mm, depth 86mm, height 90mm. IP20. 220-240V main connection, Triac dimmable.

Mounting	Product type	Indoor ceiling-mounted luminaire			
	Installation type	Ceiling-mounted			
Dimension	Length	86mm			
	Depth	86mm			
	Height	90mm			
Lamp	LED	Lumens			
	System/W	10W			
	Luminous flux nominal	DL013S/_/3K/BI	970lm	DL013S/_/3K/NE	970lm
		DL013S/_/4K/BI	970lm	DL013S/_/4K/NE	970lm
	Colour temperature CCT	3000K, 4000K			
	Colour rendering index CRI	>80			
Light	LED Lifetime	40.000 h			
	Light distribution	Direct			
	Light beam	24°, 40°, 50°			
Material	Body	Die-cast aluminium			
	Colour	White			
	Reflector	Polycarbonate chrome			
	Diffuser	Micro-prismatic			
Electrical	Driver	220-240V main connection, TRIAC dimmable			
Warranty	Warranty	2 years			
Norms	Norm compliance	EN60598-1, EN60598-2-1, EN62471, IEC/TR 62778, EN62493, EN61000-3-3, EN61000-3-2, EN61547, EN55015			

CODE CONFIGURATION

DL013S	/	*	*	/	*	*	/	*	*
		1			2			3	
1	Light beam	24 = 24°, 40 = 40°, 50 = 50°							
2	Colour temperature	3K = 3000K, 4K = 4000K							
3	Colour	BI = white, NE = black							

ACCESSORIES AVAILABLE ON REQUEST

LENS/24/DL013	Lens 24°
LENS/40/DL013	Lens 40°
LENS/50/DL013	Lens 50°