




LOOP - L01F



1 LIGHT - FIXED WITH FRAME



SPECIFICATION TEXT



Square recessed LED luminaire with 1 light, fixed optics and perimeter surface frame. Efficient flow and controlled luminance UGR<16 (25°) or UGR<19 (40°). High visual comfort CRI>90. IP20. Aluminium body available in 2 finish options, 4 polycarbonate reflector available colours. Power supply included, dimmable versions and remote control options available. Compliant with CAM EDILIZIA standards, minimum environmental criteria. (Ministerial Decree of June 23, 2022).

Mounting	Product type	Recessed fixed downlight							
	Installation type	Ceiling-mounted							
Dimension	Frame	45x45mm							
	Height	57.5mm							
	Cut-out	37x37mm							
	Minimum recessed depth	120mm							
	Plasterboard depth	min. 1mm max. 25mm							
Lamp	LED	Osram							
	LED/W	2W							
	System/W	3W							
	Luminous flux nominal	L01F/WCM/3K02/_	210lm	L01F/WCM/4K02/_	230lm	L01F/WCF/3K02/_	210lm	L01F/WCF/4K02/_	230lm
		L01F/BCM/3K02/_	210lm	L01F/BCM/4K02/_	230lm	L01F/BCF/3K02/_	210lm	L01F/BCF/4K02/_	230lm
	Luminous flux real	L01F/WCM/3K02/_	193lm	L01F/WCM/4K02/_	211lm	L01F/WCF/3K02/_	178lm	L01F/WCF/4K02/_	195lm
		L01F/BCM/3K02/_	193lm	L01F/BCM/4K02/_	211lm	L01F/BCF/3K02/_	178lm	L01F/BCF/4K02/_	195lm
	Colour temperature CCT	3000K, 4000K							
	Colour rendering index CRI	>90							
	LED Lifetime	>50.000 h L70B10 (Ta25°)							
	MacAdam	3							
	UGR	<16 (25°) - <19 (40°)							
Light	Adjustability	0° rotation / 0° tilt							
	Light distribution	Direct							
	Light beam	25°, 40°							
Material	Body	Die-cast aluminium							
	Frame	Aluminium painted white (RAL9016) or black (RAL9005)							
	Reflector	Polycarbonate, 4 colours: B black, G gold matt, M silver matt, W white							
Electrical	Driver	220-240V 50-60Hz included							
	LED current	700mA							
Warranty	Warranty	5 years							
Norms	Norm compliance	EN60598-1, EN60598-2-2, EN62471, IEC/TR 62778, EN62493, EN61000-3-3, EN61000-3-2, EN61547, EN55015							

CODE CONFIGURATION

L	*	*	*	/	*	C	*	/	*	*	*	*	/	*	*
	1		2		3		4		5		6		7		8
1	LED modules		01 = 1; 02 = 2; 03 = 3; 04 = 4; 05 = 5; 10 = 10.												
2	Adjustability		F = fixed; A = adjustable...												
3	Body colour		B = black; W = white.												
4	Light beam		M = 25°; F = 40°.												
5	Colour temperature		3K = 3000K; 4K = 4000K.												
6	Power W		(01) 2; (02) 4; (03) 7; (04) 9; (05) 11; (10) 22.												
7	Colour reflector		B = black; G = gold matt; M = silver matt; W = white.												
8	Driver**		1 = On-Off Made in Italy; 2* = PUSH/1-10V Made in Italy; 3 = DALI Made in Italy; 6 = On-Off; 9 - Wi-Fi ZIGBEE Made in Italy (Zigbee gateway, not included); 10 - Bluetooth BLL Made in Italy (by APP BLL PLUS: IOS/Android); 11 - Bluetooth CASAMBI Made in Italy (by APP CASAMBI: IOS/Android)												

** 1-2-3-9-10-11 not suitable for 01 version
* Max 4 devices PUSH button

Emergency kit available upon request

KIT/EMERGENZA/3H	Emergency kit for LED up to 3 hours
------------------	-------------------------------------