NOBILE
Italia

PIN - PN10

WALL LIGHTING







For further information please visit www.nobile.it/en/

SPECIFICATION TEXT

IP54 | A | G | W | CE | ERP COMPLIANCE

Round outdoor LED luminaire for wall-mounted installation. Indirect lighting. Die-cast aluminium body painted white (RAL9003), grey (RAL9006) or anthracite (RAL7016). Micro-prismatic glass. IK06. IP54. Diameter 120mm. 220-240V - 50/60Hz power supply included.

Mounting	Product type	**Outdoor wall-mounted luminaire**			
	Installation type	**Wall-mounted**			
Dimension	Body	**120mm**			
	Width	**120mm**			
Lamp	LED	**OSRAM**			
	System/W	**8.2W**			
	Luminous flux nominal	**PN10/3K/_**	1080lm	**PN10/4K/_**	1170lm
	Luminous flux real	**PN10/3K/_**	968lm	**PN10/4K/_**	1048lm
	Colour temperature CCT	**3000K, 4000K**			
	Colour rendering index CRI	**>80**			
	LED Lifetime	**50.000 h**			
	MacAdam	**3**			
Light	Light distribution	**Indirect**			
	Light beam	**105°**			
Material	Body	**Die-cast aluminium**			
	Colour	**A= anthracite RAL7016 , G= grey RAL9006 , W= white RAL9003**			
	Diffuser	**Micro-prismatic glass**			
IK	IK	**06**			
Electical	Operating voltage	**220-240V 50-60Hz power supply included**			
Warranty	Warranty	**3 years**			
Norms	Norm compliance	**EN60598-1, EN60598-2-1, EN62471, IEC/TR 62778, EN61000-3-3, EN61000-3-2, EN61547, EN55015**			

CODE CONFIGURATION

PN10	/	*	*	/	*
		1			**2**
1	Colour temperature	**3K** = 3000K; **4K** = 4000K.			
2	Colour	**A**= anthracite; **G**= grey; **W**= white.			

Nobile Italia S.p.A.
Viale Alexandre Gustave Eiffel, 100 Commercity Isola P.21-24 - 00148 Roma, Italia - Tel. +39 06 65002524 - info@nobile.it
Export Sales Department: Via Lavoratori Autobianchi, 1 20832 Desio (MB), Italia - Tel. +39 0362 1790030 - export.dpt@nobile.it