NOBILE
Italia

STICK - SK060/1A

BOLLARD MONO-DIRECTION





For further information please visit www.nobile.it/en/

IP54 | A | G | W | CE | ERP COMPLIANCE

SPECIFICATION TEXT

Outdoor LED bollard for installation on floor or ground. Vertical mono-direction beam. Anchoring system included. Die-cast aluminium body painted white (RAL9003), grey (RAL9006) or anthracite (RAL7016). Satin polycarbonate diffuser. IK08. IP54. Height 600mm. Neoprene H05RN-F 3x0.75mm² cable of 1500mm. 220-240V - 50/60Hz power supply included.

Mounting	Product type	**Bollard with vertical mono-direction beam**			
	Installation type	**Floor, ground**			
Dimension	Body	**60x100mm**			
	Height	**600mm**			
Lamp	LED	**OSRAM**			
	System/W	**8.5W**			
	Luminous flux nominal	**SK060/1A/3K/_**	1100lm	**SK060/1A/4K/_**	1250lm
	Luminous flux real	**SK060/1A/3K/_**	705lm	**SK060/1A/4K/_**	820lm
	Colour temperature CCT	**3000K, 4000K**			
	Colour rendering index CRI	**>80**			
	LED Lifetime	**50.000 h**			
	MacAdam	**3**			
Light	Light distribution	**Vertical mono-direction**			
Material	Body	**Die-cast aluminium**			
	Colour	**A= anthracite RAL7016 , G= grey RAL9006 , W= white RAL9003**			
	Diffuser	**Satin polycarbonate**			
	Cable	**Neoprene H05RN-F 3x0.75mm² 1500mm**			
	Anchoring system	**Stainless steel, included - KIT/SK030 to be ordered separately**			
IK	IK	**08**			
Electrical	Operating voltage	**220-240V 50-60Hz power supply included**			
Warranty	Warranty	**3 years**			
Norms	Norm compliance	**EN60598-1, EN60598-2-1, EN62471, IEC/TR 62778, EN61000-3-3, EN61000-3-2, EN61547, EN55015**			

CODE CONFIGURATION

SK060	/	**1A**	/	*	*	/	*
				1			**2**
1	Colour temperature	**3K** = 3000K; **4K** = 4000K.					
2	Colour	**A**= anthracite; **G**= grey; **W**= white.					

Accessories upon request to be ordered separately



KIT/SK030

Anchoring system for inground installation included.

Nobile Italia S.p.A.
Viale Alexandre Gustave Eiffel, 100 Commercity Isola P.21-24 - 00148 Roma, Italia - Tel. +39 06 65002524 - info@nobile.it
Export Sales Department: Via Lavoratori Autobianchi, 1 20832 Desio (MB), Italia - Tel. +39 0362 1790030 - export.dpt@nobile.it