

en

Operating voltage	220-240V AC 50Hz/60Hz
Switching capacity	400W (control gear)
Stand-by power	≤1W
Detection area	25%/50%/75%/100%*
Hold time	5s/30s/1min/3min/5min*/10min/20min/30min
Daylight threshold	2Lux/10Lux/30Lux/50Lux/80Lux/120Lux*/Disable
Microwave frequency	5.8GHz±75MHz
Microwave power	<0.3Mw
Mounting height	4m/13.12ft (ceiling mounted)
Detection range	Radius, 6m/19.68ft (ceiling mounted)
Operating temperature	-20°C-+60°C
Interfaces	L, N, N, L'
Motion detection	0.5-1.5m/s
IP rating	IP20
Warranty	5 years
Remote controlled required	UNREMOTEMWS

### Default settings\*

en t +44 (0) 1604 495 151 | f +44 (0) 1604 495 095 | e sales@collingwoodgroup.com | w collingwoodlighting.com  
Collingwood Lighting, Brooklands House, Sywell Aerodrome, Sywell, Northampton NN6 0BT, United Kingdom

fr t +32 (0)4 351 91 40 | e info@indigo-lighting.com | w www.indigo-lighting.com  
Indigo S.A. / N.V. Rue de la légende 32 G, 4141 Srimont - Belgique



Disposal of this product should be separate from household waste. Please separate these items from other types of waste and recycle them responsibly to promote the sustainable reuse of material resource. Household users should contact their local government office for details of where and how they can take these items for environmentally safe recycling.